

SERIES FF - 6201

Braided Flexible Metal Flanged Connectors (321 Stainless Steel Hose with 304 Stainless Steel Braid and Carbon Steel Plate Flanges).

TABLE 1: Sizes • Offset • Working Pressures • Weights

Expansion Joint Size: ID X Length	Stock	Lateral Offset		Working Press (PSI)		Approx. Unit Ship Weight
		Intermittent	Permanent	@70°F	@300°F	
2 X 9	S	1/8"	3/8"	455	400	9
2 X 12	S	3/4"	1"	455	400	12
2 1/2 X 9	S	1/8"	3/8"	345	303	13
2 1/2 X 10	S	1/8"	3/8"	345	303	13
2 1/2 X 10 1/4	S	3/8"	3/4"	345	303	13
2 1/2 X 12	S	3/4"	1"	345	303	13
3 X 9	S	1/8"	3/8"	289	254	14
3 X 10	S	1/8"	3/8"	289	254	14
3 X 10 5/8	S	3/8"	3/4"	289	254	14
3 X 14	S	3/4"	1"	289	254	15
4 X 9	S	1/8"	3/8"	300	264	18
4 X 10	S	1/8"	3/8"	300	264	18
4 X 11 3/4	S	3/8"	3/4"	300	264	19
4 X 16	S	3/4"	1"	300	264	20
5 X 11	S	1/8"	3/8"	220	193	25
5 X 12	S	1/8"	3/8"	220	193	25
5 X 13 5/8	S	3/8"	3/4"	220	193	27
5 X 18	S	3/4"	1"	220	193	30
6 X 11	S	1/8"	3/8"	200	176	28
6 X 12	S	1/8"	3/8"	200	176	28
6 X 14 1/8	S	3/8"	3/4"	200	176	30
6 X 20	S	3/4"	1"	200	176	34
8 X 12	S	1/8"	3/8"	190	167	52
8 X 13	S	1/8"	3/8"	190	167	52
8 X 15 3/8	S	3/8"	3/4"	190	167	64
8 X 22	S	3/4"	1"	190	167	65
10 X 13	S	1/8"	3/8"	165	145	65
10 X 14	S	1/8"	3/8"	165	145	65
10 X 17 3/4	S	3/8"	3/4"	165	145	68
10 X 24	S	3/4"	1"	165	145	75
12 X 14	S	1/8"	3/8"	125	110	105
12 X 15	S	1/8"	3/8"	125	110	105
12 X 18 3/8	S	3/8"	3/4"	125	110	110
12 X 26	S	3/4"	1"	125	110	113
14 X 14	S	1/8"	3/8"	105	92	115
14 X 15	S	1/8"	3/8"	105	92	115
14 X 20	X	3/8"	3/4"	105	92	119
14 X 28	X	3/4"	1"	105	92	126

NOTES: 1. "S" indicates stocked item.
2. "X" denotes 1-2 week shipment lead time.

website: <http://www.procoproducts.com>

